

SAFETY DATA SHEET

1. Identification

Product identifier Epic

Recommended use For Industrial Use Only

Recommended restrictions Users should be informed of the potential presence of

respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as

required under applicable regulations.

Manufacturer/Supplier information

Company name: FRC Global

Address: 1000 N. West St.

Suite 1200 #3008 Wilmington, DE 19801

Product Support/Technical Services

Phone: (514) 931-5711

Website www.FRCglobal.com

Emergency telephone number: Corporate Office: (514) 931-5711

Technical Services: (514) 931-5711

Contact E-Mail: <u>LadleDr@FRCglobal.com</u>

2. Hazard(s) identification

Classified hazards This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements.

Wear protective gloves/protective clothing/eye

protection. Dust may cause cancer.

Label elements This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements.

Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance

3. Composition/information on ingredients

Chemical Name	Common Name/Synonyms	CAS Number	%
Aluminum Oxide (Non-Fibrous)		1344-28-1	*
Mullite		1302-93-8	*
Cristobalite		14464-46-1	*
Silicon Dioxide		7631-86-9	*
Quartz (SiO2)		14808-60-7	*
Titanium Dioxide		13463-67-7	*

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or

persist.

Skin contact Wash off with soap and water. Get medical attention if

irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation

develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Direct contact with the eyes may cause temporary

irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep the victim under observation.

Symptoms may be delayed.

General information If concerned: Get medical advice. Ensure that medical

personnel are aware of the material(s) involved and take

precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Use fire-extinguishing media appropriate for surrounding

materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not available.

Special protective equipment and precautions for firefighters

Not available.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate

ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal

protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush the area with water. For waste

disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses, or onto the

ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep the formation of airborne dust to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in the original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limit

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum Oxide (Non-Fibrous)	PEL	5 mg/m3	Respirable fraction
(CAS 1344-28-1)			
Titanium Dioxide	PEL	15mg/m3	Total Dust
(CAS 13463-67-7)			

US OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form	

Cristobalite	TWA	0.15 mg/m3	Total dust.
(CAS 14464-46-1)		0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Quartz (SiO2)	TWA	.03 mg/m3	Total dust.
(CAS 14808-60-7)			
Silicon Dioxide	TWA	0.8 mg/m3	
(CAS 7631-86-9)		20 mppcf	

US ACGIH Threshold Limit Values

Components	Туре	Value	Form
Aluminum Oxide (Non-Fibrous)	TWA	1 mg/m3	Respirable fraction.
(CAS 1344-28-1)			
Cristobalite	TWA	0.025 mg/m3	Respirable fraction.
(CAS14464-46-1)			
Mullite	TWA	1 mg/m3	Respirable fraction.
(CAS 1302-93-8)			
Quartz	TWA	1mg/m3	Respirable fraction.
(14808-60-7)			
Titanium Dioxide	TWA	10mg/m3	Respirable fraction
(CAS 13463-67-7)			

US NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Cristobalite	TWA	3 fibers/cm3	Fiber.
(CAS 14464-46-1)		3 fibers/cm3	Dust.
		5 mg/m3	Fiber, total
		5 mg/m3	Fibers, total dust
Quartz (14808-60-7)	TWA	.05mg/m3	Respirable dust.
Silicon Dioxide	TWA	6 mg/m3	
(CAS 7631-86-9)			

Biological limit values Exposure guidelines

No biological exposure limits noted for the ingredient(s). Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

If contact is likely, wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical-resistant gloves.

Other Wear suitable protective clothing. Use of an impervious

apron is recommended.

Respiratory protection Use a NIOSH/MSHA-approved respirator if there is a risk of

exposure to dust/fume at levels exceeding the exposure

limits.

Thermal hazards Wear appropriate thermal protective clothing, when

necessary.









General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. Form Solid.

Color

Odor

Odor threshold

pH

Not available.

Initial boiling point and boiling range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available. Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available. Not available.

Auto-ignition temperature
Decomposition temperature

Viscosity

Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal

conditions of use, storage, and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction is known under conditions of

normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Fluorine. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to

industrial application exposure. Contact your sales

representative for clarification.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with the eyes may cause temporary

irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical, and toxicological characteristics:

Direct contact with the eyes may cause temporary

irritation.

Information on toxicological effects

Acute toxicity Not Classified LC50 > 5000 mg/kg

LD50(dermal) > 2000 mg/kg

LD50(oral) 500.0000000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with the eyes may cause temporary

irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data is available to indicate product, or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However, in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust, and organic fibers, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Silicon Dioxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to

humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human

Carcinogen.

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure

may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

the environment.

Persistence and degradability

Bio-accumulative potential

Mobility in soil

Other adverse effects

No data is available on the degradability of this product.

No data available. No data available.

No other adverse environmental effects (e.g. ozone

depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or

disposed of, is not hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste.

Hazardous waste code Not applicable.

Waste from residues / unused products

Not available.

Contaminated packaging Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as

defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where

required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Chemical

Not listed.

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Aluminum Oxide (Non-Fibrous)	1344-28-1	*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not Regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR

68.130) Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US Massachusetts RTK - Substance List

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Quartz (SiO2) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9) Titanium Dioxide (CAS 13463-67-7)

US New Jersey Worker and Community Right-to-Know Act

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Quartz (SiO2) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9) Titanium Dioxide (CAS 13463-67-7)

US Pennsylvania Worker and Community Right-to-Know Law

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1)

Quartz (SiO2) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9) Titanium Dioxide (CAS 13463-67-7)

US Rhode Island RTK Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

US California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respect to product liability, rests solely upon the purchaser thereof.

Prepared by: FRC Global October 2020

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided and believed to be correct as of the issue date. However, FRC Global makes no representation or warranties and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose before use. FRC Global will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or misuse of the information contained herein.

End of Safety Data Sheet