

INFORMATION BULLETIN

Icon 5

DESCRIPTION: Magnesia alumina carbon brick, resin bonded, with

very high erosion and slag resistance. With

antioxidants.

USES INCLUDE: Electric furnace sidewalls.

Ladle/furnace bottoms. BOF working linings.

CHEMICAL ANALYSIS: (TYPICAL CHEMICAL ANALYSIS)

(Approximate % by weight)

 $\begin{array}{cccc} \text{MgO} & 85.0\% \\ \text{Al}_2\text{O}_3 & 10.0\% \\ \text{Fe}_2\text{O}_3 & 1.9\% \\ \text{CaO} & 1.0\% \\ \text{SiO}_2 & 1.0\% \end{array}$

TYPICAL AS RECEIVED PROPERTIES:

Apparent Porosity (%): 2.5

Bulk Density, orig g/cm³ (lb/ft³): 3.0 (187) Cold Crushing Strength (psi): 6000 Carbon (%) 5.0 - 20.0

The values reported above are average values derived from production data encompassing many different sizes and shapes. Actual data will vary to a small degree naturally and as a function of size and shape. This form is not intended to be used for purposes of specification; it is informational only.

Version 20.11

Phone: 1-800-609-5711 www.FRCglobal.com