



SAFETY DATA SHEET

1. Identification

Product identifier MGO Briquette 65
Recommended use For Industrial Use Only
Recommended restrictions Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Supplier information

Company name: Fedmet Resources Corporation
Address: 1000 N. West St.
Suite 1200 #889
Wilmington, DE 19801
Product Support/Technical Services
Phone: (514) 931-5711
Website www.fedmet.com

Emergency telephone number: Corporate Office: (514)931-5711
Technical Services: (514)931-5711
Contact E-Mail: ladledr@fedmet.com

2. Hazard(s) identification

Physical hazards Not classified
Health hazards Carcinogenicity Category 1A
Environmental hazards Not classified
OSHA defined hazards Not classified

Label elements



Signal word Danger
Hazard Statement May cause cancer.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection.
Response If concerned: Get medical advice/attention.

Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations
Hazard(s) not otherwise Classified (HNOC)	None Known.
Supplemental information	Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Chemical Name	Common Name/Synonyms	CAS Number	%
Magnesium Oxide		1309-48-4	63-65
Silica	Quartz	14808-60-7	12 max
Calcium Oxide		1305-78-8	5%
Iron Oxide	Below reportable level	1309-37-1	
LOI (Lost of Ignition)	20-30% typical – 30% max		

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Dust may cause temporary irritation of upper respiratory tract and slight irritation of eyes and nose. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Irritation, drying or chapping. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In large quantities and rarely, irritation, nausea and gastrointestinal upset. Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
-------------------------------------	---

Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Not available.
Special protective equipment and precautions for firefighters	Not available.
Special Remarks on Fire Hazards	not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Wear appropriate protective equipment and clothing during clean-up. Collect spill using a vacuum cleaner with a HEPA filter. Place in a closed container. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

<i>Components</i>	<i>Type</i>	<i>Value</i>	<i>Form</i>
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m ³	Total particulate.
Iron oxide (1309-37-1)	TWA	10mg/m ³	Respirable fraction
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m ³	

US. OSHA Table Z-3 (29 CFR 1910.1000)

<i>Components</i>	<i>Type</i>	<i>Value</i>	<i>Form</i>
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

<i>Components</i>	<i>Type</i>	<i>Value</i>	<i>Form</i>
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m ³	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025mg/m ³	Respirable fraction
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

<i>Components</i>	<i>Type</i>	<i>Value</i>	<i>Form</i>
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m ³	
Quartz (SiO₂) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge, full face piece, dust and mist filter.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Use of an impervious apron is recommended.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.



General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state solid
Form granule or powder.
Color Varies.

Odor Odorless

Odor threshold Not available.

pH Not available

Melting point/freezing point Not available

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative Density Not available

Solubility(ies)

Solubility (water) Not available

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity reacts vigorously with halogens and strong acids

Chemical stability Unstable under the following conditions, absorbs easily humidity and carbon dioxide when contact with atmosphere.

Possibility of hazardous reactions

Conditions to avoid

Incompatible materials

reacts violently with interhalogens

Contact with incompatible materials.

Interhalogens, sublimed sulfur and magnesium or aluminum powder. Powerful oxidizers. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales representative for clarification.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact

Dust or powder may irritate the skin.

Eye contact

Dust may irritate the eyes.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics:

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. Higher exposures may cause difficulty breathing, congestion, and chest tightness.

Information on toxicological effects

Acute toxicity

Not available.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

May cause respiratory problems

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However, in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing

regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (SiO₂) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO₂) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Developmental effects

Quartz (SiO₂) 0

Developmental effects - EU category

Quartz (SiO₂) 0

Embryo toxicity

Quartz (SiO₂) 0

Reproductively

Quartz (SiO₂) 0

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Eco toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bio accumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be

determined in arrangement with your waste disposal partner or the responsible authority.

Waste from residues / unused products

Not available.

Contaminated packaging

Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Packaging Group

Not classified

Bulk Transport

Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Chemical No

SARA 313 (TRI reporting)

<i>Chemical Name</i>	<i>CAS number</i>	<i>% by wt.</i>
----------------------	-------------------	-----------------

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not Regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Magnesium oxide (CAS 1309-48-4)

Quartz (SiO₂) (CAS 14808-60-7)

Calcium Oxide (CAS 1305-78-8)

US. New Jersey Worker and Community Right-to-Know Act

Magnesium oxide (CAS 1309-48-4)

Quartz (SiO₂) (CAS 14808-60-7)

Calcium Oxide (CAS 1305-78-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Magnesium oxide (CAS 1309-48-4)

Quartz (SiO₂) (CAS 14808-60-7)

Calcium Oxide (CAS 1305-78-8)

US. Rhode Island RTK

US. California Proposition 65

This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO₂) (CAS 14808-60-7)

Listed: October 1, 1988

16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respects to products liability, rest solely upon the purchaser thereof.

Prepared by: Fedmet Resources Corporation

Date: April, 2020

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided, and believed to be correct as of the issue date. However, Fedmet Resources Corporation makes no representation or warranties, and assumes no responsibility as to the completeness and accuracy thereof Users must make their own determination as to the suitability of the product for their purpose prior to use. Fedmet Resources Corporation will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or the misuse of the information contained herein.

End of Safety Data Sheet